

Leak Sealer
SDS No. 060

SAFETY DATA SHEET

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Datasheet Number: Product Name: 0Leak Sealer60 1. 1. 0

1.2. Relevant identified uses of the substance or mixture and uses advised against

Concentrated sealing agent for swimming pools and spas.

1.3. Details of the supplier of the safety data sheet

Name of Supplier: Deep Blue Pool Supplies

Address of Supplier: Box 8899 Hermitage, Corsham, SN13 8DT

Telephone: +44 (0) 3330 907094

Email: help@deepbluepoolsupplies.co.uk

1.4 Emergency telephone number 09062 655005

2. Hazards identification

2.1 Classification of the substance or mixture

Classification under CLP: STOT SE 3: H335; Eye Dam. 1: H318; Skin Irrit. 2: H315

Most important adverse effects: Causes skin irritation. Causes serious eye damage. May cause respiratory irritation

Leak Sealer SDS No. 060

2.2 Label Elements:

Label elements:

Hazard statements: H315: Causes skin irritation.

H318: Causes serious eye damage.

H335: May cause respiratory irritation.

Signal words: Danger

Hazard pictograms: GHS05: Corrosion
GHS07: Exclamation mark



Precautionary statements: P261: Avoid breathing dust/fumes/gas/mist/vapours/spray.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P302+350: IF ON SKIN: Gently wash with plenty of soap and water.

P304+340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337+313: If eye irritation persists: Get medical.

2.3 Other Hazards:

- This product is not identified as a PBT/vPvB substance.

3. Composition/information on ingredients 3.1 Substances:

Chemical identity: SODIUM SILICATE

REACH registered number(s): MIXTURE **Contains:** Mixture of listed substances with non hazardous additions.

4. First Aid Measures:

4.1 Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water.

Eye contact: Check for and remove any contact lenses. Open eyes wide apart. Rinse opened eye with plenty of water for at least 15 minutes. Get medical attention.

Ingestion: Wash out mouth with water. Do not induce vomiting. If conscious, give half a litre of water

to drink immediately. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so.

Leak Sealer SDS No. 060

4.2 Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be pain and redness. The eyes may water profusely. There may be severe pain. The vision may become blurred. May cause permanent damage.

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. **Delayed / immediate effects:** Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

- Eye bathing equipment should be available on the premises.

Section 5: Fire-fighting measures

5.1 Extinguishing media

- Suitable extinguishing media for the surrounding fire should be used. Use water

spray to cool containers. **5.2 Special hazards arising from**

the substance or mixture 5.3- Advice for firefighters

Section 6: Accidental release measures

- In combustion emits toxic fumes

Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions: Mark out the contaminated area with signs and prevent access to unauthorised personnel. Do not attempt to take action without suitable protective clothing - see section 8 of SDS. Turn leaking containers leak-side up to prevent the escape of liquid.

6.2 Environmental Precautions- Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3 Methods and material for containment and cleaning up

- Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

6.4 Reference to other sections -

Refer to section 8 of SDS.

Section 7: Handling and storage

7.1

-Precautions for safe handling Avoid direct contact with the substance. Ensure there is sufficient ventilation of

the area.

- Avoid the formation or spread of mists in the air

7.2 Conditions for safe storage, including any incompatibilities -

Store in a cool, well ventilated area. Keep container tightly closed.

7.3 Specific end use(s)- No information available.)

Section 8: Exposure controls/personal protection

8.1 Control parameters

Hazardous ingredients:

SODIUM SILICATE

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
EU	-	2 mg/m ³	-	-

8.2 Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Protective gloves.

Eye protection: Tightly fitting safety goggles. Ensure eye bath is to hand.

Skin protection: Protective clothing.



Respirator



Goggles



Gloves



Suit

Section 9. Physical & Chemical Properties

9.1 Information on basic physical and chemical properties

State: Liquid

Colour: Colourless

Odour: Odourless

Relative density: 1.500

pH: >8

9.2 Other information

- No data available.

Section 10. Stability and reactivity

10.1 -Reactivity Stable under recommended transport or storage conditions.

10.2 -Chemical stability Stable under normal conditions.

10.3 --Possibility of hazardous reactions Decomposition may occur on exposure to conditions or materials listed below. Hazardous reactions will not occur under normal transport or storage conditions.

10.410.5 -Incompatible materials-Conditions to avoid Heat Strong oxidising agents. Strong acids.

10.6 Hazardous Decomposition Products

- In combustion emits toxic fumes.

Section 11. Toxicological information

11.1 Information on toxicological effects

Toxicity values:

Route	Species	Test	Value	Units
ORAL	RAT	LD50	>2000	mg/kg
DERMAL	RAT	LD50	>2000	mg/kg

Hazardous ingredients:

SODIUM SILICATE

ORAL	RAT	LD50	1300 - 2200	mg/kg
------	-----	------	-------------	-------

Relevant hazards for substance:

Hazard	Route	Basis
Skin corrosion/irritation	DRM	Hazardous: calculated
Serious eye damage/irritation	OPT	Hazardous: calculated
STOT-single exposure	INH	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be pain and redness. The eyes may water profusely. There may be severe pain. The vision may become blurred. May cause permanent damage.

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure. **Section**

12. Ecological information

12.1 Toxicity

Ecotoxicity values:

Species	Test	Value	Units
DAPHNIA	48H EC50	>100	mg/l

12.2 Persistence and degradability- No information available

12.3 Bioaccumulation Potential 12.4 Mobility in soil 12.5 -Results of PBT and vPvB assessment 12.6 Other Adverse Effects

- No bioaccumulation potential.
- Readily absorbed into soil.

This product is not identified as a PBT/vPvB substance.

- No data available.

Section 13. Disposal considerations

13.1 Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal

company.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14. Transport information Section 15. Regulatory information

Transport class: This product does not require a classification for transport.

15.1.2 Chemical Safety Assessment1 -Safety, health and environmental regulations/legislation specific for the substance or mixture Section 16. Other information

15 Not applicable

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 453/2010.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: H315: Causes skin irritation.

H318: Causes serious eye damage.

H335: May cause respiratory irritation.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of Deep Blue Pool Supplies limited knowledge and belief, accurate, and reliable as of the date of authorisation of this safety data sheet. However, no representation, warranty or guarantee is made as to its accuracy, reliability or completeness. It is the user's responsibility to be satisfied as to the suitability and completeness of such information for the product as used.

Leak Sealer
SDS No. 060



Date of Last Change: 13/09/2016